The Oil Report

Jan. 2004

"Oil the News That's Fit to Print!"



Spotlight on... the Nature of Oil

by Jim Stark

Long before Ray Kroc and others dotted the landscape with fast-food franchises, we had drive-in restaurants with limited menus that laid the foundation for today's fast-food venues. This was in the 1950s and early 1960s. The drive-ins had both a drive-up (where you ate in your car with a tray attached to the window) and inside service, and the restaurants catered mostly to the tastes of young people. That is probably one of the reasons why the drive-in didn't really make it in the long run — young people, as much as they loved to work on their social skills at places like drive-ins, were, in that period, remarkably broke.

I frequented a drive-in called Dale's. The seating in the dining room was at lopsided, linoleum-topped tables surrounded by cracked, vinyl-clad booths. These restaurants (always at the lower end of the food-service chain) were not air-conditioned. On a humid summer evening you could observe a unique phenomenon that demonstrated an interesting property of oil.

As we sat there joking with friends, our cold glasses of soda would sweat, causing water to pool beneath the glasses. Before your very eyes, your glass, as if by magic, would start to move across the uneven tabletop. Water would collect in a pool at the base and underneath the glass, and the water's surface tension was strong enough to overcome the weight of the glass and its contents. The water became a lubricant.

Oil has the same ability (only to a greater extent) to collect in a pool on a surface or between two parts and keep the surfaces from touching. This is one of the properties of oil that makes it so useful: It coats and protects parts, virtually eliminating friction between surfaces.

The Liquid That Acts Like a Solid

Oil has several purposes in a machine. It lubricates, cleans, and cools, carrying heat and debris away from surfaces of the parts it lubricates. Though a machine such as an internal combustion engine is made of metal parts, none of the parts actually touch, thanks to the oil. (If you hear a ticking or knock from your engine, that means parts are probably overcoming the lubricant and touching, and the engine may be headed toward failure.)

Oil, like any liquid, is non-compressible. It is this property that allows hydraulic systems to work. If you put oil in a closed vessel like a cylinder and press down on it with a piston, the oil will apply equal pressure to all the surfaces containing it. You can apply as much pressure as you want, but the oil will not compress. In this respect, the oil acts like a solid:

Do you use the 20-pack?

If you already use our 20-pack box for your industrial oil samples, then feel free to skip this article. If you don't know what we're talking about, read on! Blackstone's 20-pack of sampling kits is especially designed for industrial oil sampling, and it may be perfect for your needs.



The 20-pack is basically a box containing 20 oil sample bottles. If you have many machines to sample at once, the 20-pack allows you to do so easily and without filling out a lot of paperwork. Just take the box from machine to machine and write the unit ID on the lid of the bottle. When you've got all the samples you need, close up the box and send it back to us! It's perfect for high-volume sampling and eliminating paperwork. If you're not using our 20-packs yet, let us know you'd like to switch!



What is this and what does it have to do with your oil sample? To find out, read our new article on how oil analysis works by <u>clicking here.</u>



although it is constantly flowing, it serves as a "wall" between the machine's parts, keeping them from touching.

Imagine the oil in your engine. It's under pressure, so it's acting like a soft, solid cushion and keeping the crankshaft from touching the friction bearings in which it rotates. In this scenario, the "solid" nature of the oil can be helpful or harmful, depending on its condition. When we find wear metals in your oil, it's the oil that's causing the parts to wear, not (usually) contact between metal parts. If the cushion of oil between the rotating shaft and the bearings is clean, it's like a slick tongue of Teflon. If it's dirty, it acts more like an abrasive pad. That is why it is vital to keep your oil clean if you expect to get long life from an engine or any other type of oil-wetted machine.

Well, you might think, that is why we use oil filters. And indeed, oil filters do help keep the oil clean, but only a little. Early engines didn't have filtered systems, and there was debate for many years after they were introduced whether they were really necessary and whether people would be willing to pay for them. Filters can only filter out the largest particles from the oil. The finer particles pass on through and cause abrasion at the oil-wetted parts. Dirty oil in an unfiltered system could be thought of as a 50-grit pad at the bearings. Dirty oil in a filtered system would still be a 220-grit pad.

The Importance of Viscosity?

The viscosity, or thickness of the oil, is not nearly as important as many people think. Oil retains its nature no matter what thickness it is. Think about this: automakers are continually recommending lighter multi-grade oil in new engines. The reason is increased efficiency. It takes power to pump oil through an engine, and the lighter the oil, the less power required to pump it. The oil's ability to act like a solid and protect parts is not related to its thickness.

If that doesn't sound quite right, consider this: The gears in a heavy duty Allison automatic transmission are doing the same work as the same machine equipped with an Eaton manual transmission. Due to the hydraulics of the automatic, it runs on a 10W automatic transmission oil. But the manual transmission uses a very thick (sometimes up to 90W) gear lube oil. The gears of both types of transmissions will have a similar life span. We don't find any significant differences in wear, regardless of oil thickness.

Oil's Fourth Function

Oil is a wonderful substance that allows machines to work. It lubricates, cleans, and cools. If you use oil analysis, your oil has a fourth function too: The ability to provide information about how a system is wearing. Machines of similar manufacture will wear similarly. The wear levels present in a machine's oil can provide useful information about the unit's mechanical health. A poorly wearing machine will fail sooner. A really badly wearing machine may be in the process of failing, but if you catch the problem in time, you might be able to fix it, giving the engine new life.

Oil analysis is a relatively new technology compared to the many decades the industrial revolution has been with us. As its benefits become more clearly understood, we are only left to wonder, why didn't someone think of this sooner?

Report of the Month

What's wrong with this gear lube oil sample? See the caption below for an explanation. Don't look right away -- take a good look at the report first.

(To learn where the various elements might be coming from, <u>click here</u>.)

MI/HR ON OIL	432	UNIT/ LOCATION AVERAGES	408	360	336	312	UNIVERSAL AVERAGES
MI/HR ON UNIT							
SAMPLE DATE	10/28/03		04/27/03	10/23/02	4/22/02	10/20/01	
ALUMINUM	0	0	0	0	0	0	
CHROMIUM	0	0	0	0	0	0	
IRON	19	26	24	21	18	20	67
COPPER	0	1	0	0	0	1	2
LEAD	1	2	1	1	2	1	2
TIN	0	0	0	0	0	0	:
MOLYBDENUM	0	0	0	0	0	0	(
NICKEL	0	0	0	0	0	0	(
POTASSIUM	0	1	0	0	0	0	(
BORON	216	192	233	206	212	206	43
SILICON	8	13	8	7	7	10	93
SODIUM	2	2	2	2	2	2	48
CALCIUM	5	9	5	5	5	6	326
MAGNESIUM	0	0	0	0	0	0	40
PHOSPHORUS	861	848	813	882	846	867	375
ZINC	7	32	10	8	10	11	277
BARIUM	0	1	0	0	0	0	13

VALUES SHOULD BE VALUES Output Contemporation	ß	TEST	CST VISCOSITY @ 40 C	SUS VISCOSITY@ 100 C	cST VISCOSITY@ 100 C	SUS VISCOSITY@ 210 F	FLASHPOINT IN F	FUEL %	ANTI- FREEZE %	WATER %	INSOLUBLES %
VALUES 78.8 420 0.0 TR		SHOULD				68-82	>405	-	-	<0.1	<0.6
		VALUES				78.8	420	-	-	0.0	TR

It was a trick question -- nothing is wrong with this oil sample! In fact, this is a perfect oil analysis report. When we are trying to determine whether a machine is normal, we not only compare the sample data to universal averages (which show typical wear for that type of machine), but we look to see whether the oil samples are producing steady wear trends. This machine, containing 80W/90 lube oil, is wearing perfectly. We couldn't find a thing wrong with this oil sample. We thought you might enjoy seeing a perfect report for once, but don't worry -- you'll find a wretched one again in the next issue of *The Oil Report*.

Want In?

If you received an email from us with links to this newsletter, you are already on our mailing list & will continue to receive *The Oil Report* unless you opt out. If you are not on our mailing

Want Out?

If you would like to unsubscribe to this newsletter, please <u>click here</u> list and would like to subscribe, please <u>click</u> <u>here</u> and send us an email.

We have three different versions of this newsletter: aircraft, industrial, and gas/diesel engine. Please let us know which one you'd like. and send us a blank e-mail.

Your name will be removed from our mailing list.

<u>Home</u> <u>About Blackstone</u> Talk About Oils <u>Auto</u> <u>Truck</u> <u>Industrial</u> <u>Aircraft</u> <u>Report Explanation</u> <u>Free Test Kit</u> <u>Links</u> <u>Contact Us</u> <u>FAQ</u>

© 1999-2004 <u>Blackstone Laboratories</u> 4929 South Lafayette Street, Fort Wayne IN 46806 (260) 744-2380 <u>bstone@blackstone-labs.com</u>